XP-002099541

1/1 - (C) WPI / DERWENT
AN - 98-481658 ç42!
AP - çDiv ex! AU940079059 941128; AU980069862 980603
PR - AU940079059 941128; AU980069862 980603
TI - Multiple layer, cook-in laminate for food products - has food-contacting and sealing layer comprising LLDPE, low density ethylene-alpha-olefin copolymer and anti-block agent
IW - MULTIPLE LAYER COOK LAMINATE FOOD PRODUCT FOOD CONTACT SEAL LAYER COMPRISE LLDPE LOW DENSITY ETHYLENE ALPHA OLEFIN COPOLYMER ANTI BLOCK AGENT
IN - COOK H J
PA - (GRAC ) GRACE & CO-CONN W R
PN - AU6986298 A 980730 DW9842 B32B27/08 Eng 024pp
ORD - 1998-07-30
IC - B32B27/08
FS - CPI;GMPI
DC - A17 A23 A92 G03 P73
AB - AU9869862 The laminate comprises 5-95 wt.% of a linear low density polyethylene (LLDPE), 5-95 wt.% of an ethylene/ alpha -olefin copolymer of density less than 0.915 /cc, and 0-2 wt.% of an anti-block agent. The food-contacting and sealing layer is corona treated. Also claimed is a method of making the above film comprising coextruding an inner sealing layer comprising the above, a barrier layer and a polyamide abuse layer, quenching the coextruded film, and corona treating the sealing layer.
- USE - For packaging products so that they can be pasteurised or cooked in the packaging.
- ADVANTAGE - The material is optionally heat-shrinkable under pasteurising conditions to provide an attractively packaged pasteurised food product. The corona treated sealing layer provides excellent protein adhesion during cook-in, e.g. to strip the skin from cooked turkey meat with the packaging.
- (Dwg.1/1)